



Y S I Environmental

Distributed by:

Lab Unlimited
CARL STUART GROUP

Tallaght Business Park
Whitestown
Dublin 24
Ireland

Unit 59, Frimley House
35 High Street
Frimley, Surrey
GU16 7JQ

Tel: (01) 4523432
Fax: (01) 4523967
E-mail: info@labunlimited.com
Web: www.labunlimited.com

Tel: 08452 30 40 30
Fax: 08452 30 50 30
E-mail: info@labunlimited.co.uk
Web: www.labunlimited.co.uk

YSI Pro30 Conductivity Instrument

Handheld Conductivity, Salinity, Specific Conductance, TDS (total dissolved solids), Temperature



Rugged and reliable, the YSI Pro30 is ideal in any field application for the measurement of conductivity. The Pro30 features user-replaceable cables in lengths up to 30-meters, 50 data set memory, and a simple calibration routine. True field performance is verified with the IP-67 waterproof and impact resistant case - drop tested at 1-meter. Additionally, the YSI super-stable 4-electrode conductivity cell is so reliable it is built directly into the 2-year warranty cable.

- 3-year instrument; 2-year cable and sensor warranty
- User-replaceable cables. Conductivity sensor built into cable. Choose among 1-, 4-, 10-, 20-, or 30-meter cables.
- Fast cal routine allows easy calibrations with the press of a button. Remembers the previous calibration values and simply walks you through the routine.
- Stores 50 data sets; no need to write down data
- Graphic, backlit display and glow in the dark keypad
- Tough. IP-67, impact-resistant, waterproof case even without the battery cover. Rubber over molded case provides extra durability.
- Rugged, military spec connectors. Bayonet style with keyed-quarter-turn lock.
- Super-stable, weighted 4-electrode conductivity sensor is built in for true field performance and designed for rugged conditions. Easily cleaned with a conductivity cleaning brush.

Ideal replacement for the YSI Model 30!

Pure
Data for a
Healthy
Planet.®

A rugged, cost-effective handheld designed for true field performance



Scan this QR code to watch the 90 second video Spec Sheet on the Pro30.

www.YSI.com/pro30



+1 937 767 7241

800 897 4151 (US)

www.yssi.com

environmental@yssi.com

SonTek/YSI
+1 858 546 8327
inquiry@sonstek.com

YSI Gulf Coast
+1 225 753 2650
environmental@yssi.com

YSI Hydrodata (UK)
+44 1462 673 581
europe@yssi.com
ireland@yssi.com

YSI Abu Dhabi Co. Ltd.
+971 2 56 31 316
samer@nanotech.co.jp

YSI Middle East (Bahrain)
+973 17536222
halsalem@yssi.com

YSI (Hong Kong) Limited
+852 2891 8154
hongkong@yssi.com

YSI (China) Limited
+86 532 575 3636
beijing@yssi-china.com

YSI Nanotech (Japan)
+81 44 222 0009
nanotech@yssi.com

YSI Australia
+61 7 390 17233
acorbett@yssi.com

YSI South Asia
+91 989 122 0639
sham@yssi.com

YSI Brazil
+55 48 9942 7840
psterling@yssi.com

ISO 9001
ISO 14001

Pure Data for a Healthy Planet and
Who's Minding the Planet? are registered
trademarks of YSI Incorporated.

©2012 YSI Incorporated
Printed in the USA 0112 W49-01



Specifications are subject to change.
Please visit YSI.com to verify all specs.



YSI incorporated
Who's Minding
the Planet?™

Pro30 System Specifications (instrument w/ cable and sensor)

Conductivity (mS, µS)	Sensor Type Range Accuracy Resolution	Four-electrode cell 0 to 200 mS/cm (auto range) 1-m or 4-m cable, ±0.5% of reading or 1.0 µS/cm, whichever greater; 0.0001 to 0.1 mS/cm (range dependent)
Salinity (ppt, PSU)	Range Accuracy Resolution	Calculated - 0 to 70 ppt ±1.0% of the reading or 0.1 ppt, whichever is greater 0.1 ppt
Temperature (°C, °F)	Range Accuracy Resolution	-5 to 55°C (23°C to 131°C) ±0.2°C 0.1°C
Total Dissolved Solids (TDS) (kg/L, g/L)	Range Accuracy Resolution	Calculated - 0 to 100 g/L TDS constant range 0.30 to 1.00 (0.64 default) Dependent on temp and conductivity; calculated from those parameters 0.001, 0.01, 0.1 g/L

Pro30 Instrument Specifications

Conductivity	±0.5% of reading or 1.0 µS/cm, whichever greater
Size	8.3 cm width x 21.6 cm length x 5.7 cm depth (3.25 in. x 8.5 in. x 2.25 in.)
Weight with batteries	475 grams (1.05 lbs.)
Power	2 alkaline C-cells providing 400 hours of battery life; low battery indicator on Pro30
Cables	1- 4- 10- 20- and 30-m lengths (3.28, 13.1, 32.8, 65.6 ft.)
Warranty	3-year instrument; 2-year cable and sensor
TDS Constant Range	Adjustable; 0.3-1.0
Conductivity Reference Temp	Adjustable; range 15°C to 25°C
Specific Conductance Temp Comp	Adjustable; 0 to 4%
Data Memory	50 data sets
Languages	English, Spanish, German, French
Certifications	RoHS, CE, WEEE, IP-67, 1-meter drop test

Pro30 Ordering Information (Order items separately*)

60530	Pro30 Handheld instrument
60530-X	1- 4- 10- 20- or 30-m cable with Cond/temp sensors (cable management kit included on all except 1-meter)

Accessories Ordering Information

603075	Large, Soft-sided carrying case
603074	Hard-sided carrying case
603162	Small, Soft-sided carrying case (accommodates up to 10-meter cables)
603069	Belt clip to attach instrument to belt
603070	Shoulder strap
038213	Conductivity cell cleaning brush
063517	Ultra clamp (attach to instrument to secure it to a desk, boat, etc)
063507	Small tripod (attach to instrument to sit on any flat surface)
626444	Lab Dock (instrument dock)
603062	Cable management kit (included with 4- 10- 20- and 30-m cables)
605978	Cable weight, 4.9 oz., attach to stainless steel tip
3161	1,000 us/cm calibrator; quart
3163	10,000 us/cm calibrator; quart
3165	100,000 us/cm calibrator; quart
3167	1,000 us/cm calibrator; 8 each pints
3168	10,000 us/cm calibrator; 8 each pints
3169	50,000 us/cm calibrator; 8 each pints

* Conductivity sensors are built into the cable and are included with all cables.



603162 carrying case



603069 belt clip



603070 shoulder strap



603074 hard carrying case