



a xylem brand



**Parameters:**

pH

Temperature

mV/ORP/Redox (oxidation reduction potential)

**EcoSense pH100A pH/ORP/mV/Temperature**  
**Accurate, economical, handheld measurements**

The EcoSense® line of compact, handheld instruments provides the most accurate data in the most affordable format. The instruments feature an easy-to-use interface, one-hand operation, IP67 waterproof case, and low cost of ownership over the life of the product. The pH100A measures pH, mV/ORP and temperature with the following features:

- IP67 Waterproof housing
- 1-year instrument warranty
- Internal buffer recognition (US or NIST buffer sets)
- Auto/Manual temperature compensation
- Electrode offset recognition
- Low battery indicator with 1000 hour battery life
- Displays electrode efficiency
- Autolock mode holds stable readings on display
- Auto shutoff function after 30 minutes of inactivity
- 50 data set memory

The EcoSense pH100A is also available as a kit with a 1- or 4-meter cable.



The pH100A is designed for quick, accurate results in an economical platform. The ability to measure pH, mV/ORP, and temperature in a simple, compact handheld allows the instrument to be used in multiple applications. With a one-year instrument warranty, six-month electrode warranty, calibration backup, and a variety of cable/sensor options (glass bulb, flat tipped, and piercing tipped), the pH100A will fit your needs.

Distributed by:   <b>Lab Unlimited</b> CARL STUART GROUP	Tallaght Business Park Whitestown Dublin 24 Ireland	Unit 59, Frimley House 35 High Street Frimley, Surrey GU16 7JQ
	Tel: (01) 4523432 Fax: (01) 4523967 E-mail: info@labunlimited.com Web: www.labunlimited.com	Tel: 08452 30 40 30 Fax: 08452 30 50 30 E-mail: info@labunlimited.co.uk Web: www.labunlimited.co.uk

## pH100A System Specifications (Instrument, Probe, and Cable)

Temperature	Range	-10 to +120°C (14 to 248°F)
	Resolution	0.1°C
	Accuracy	±0.3°C ±1 digit
pH	Range	-2 to 16 units
	Resolution	0.01 unit
	Accuracy	±0.1% ±2 digit
mV	Range	-1999 to +1999 mV
	Resolution	1 mV
	Accuracy	±0.1% ±1 digit

## pH100A Additional Specifications

### Operating range

Temperature	0° to 50° C (32 to 122°F)
Relative Humidity	up to 95%

Water rating IP67 waterproof

Size 78 mm wide (widest point) x 184 mm long x 37 mm deep (3.1 in. x 7.25 in. x 1.45 in.)

Weight with battery 272 grams (0.6 lb.)

ATC Probe Thermistor, 10kΩ / 25° C

Battery One 9 volt included with purchase; 1000 hour battery life

pH temp compensation Auto/Manual -10.0° C to 120.0°C (14 to 248°F)

pH buffer recognition US (4.00, 7.00, & 10.00 at 25°C or 4.00, 7.02 & 10.06 at 20°C) or NIST (4.01, 6.86, & 9.18 at 25°C or 4.00, 6.87 & 9.23 at 20°C)

pH calibration temp 0°C to 60°C (32 to 140°F)

pH offset recognition ±90 mV at pH 7.00 or 6.86

pH slope recognition ±30% at pH 4.00, 4.01, 9.18, or 10.01

Calibration back-up Yes

Audio feedback Yes, all keys

Autolock feature Yes

Memory 50 data set reviewable memory

Auto shutoff Automatically powers off after 30 minutes of inactivity

## pH100A Ordering Information (order items separately or as a kit)

pH100A	pH100A pH, mV and temperature instrument only
pH100ACC-01	pH100A instrument, 1-meter cable and electrode, hard-sided carrying case kit
pH100ACC-04	pH100A instrument, 4-meter cable and electrode, hard-sided carrying case kit
100-1	1-meter waterproof Y-cable with combo pH electrode and temperature
100-4	4-meter waterproof Y-cable with combo pH electrode and temperature
110-1	1-meter pH laboratory grade cable and electrode
111-1	1-meter pH piercing tipped, double-junction cable and electrode
112-1	1-meter pH flat tipped, double-junction cable and electrode
115-1	1-meter ORP laboratory grade cable and electrode
130-1	1-meter temperature cable and probe
606031	Hard-sided, plastic carrying case with form fitted foam insert; 31.75 x 22.86 x 9.4 cm (12.5 x 9 x 3.7 in)
160	pH 4, 7, 10 electrode simulator (ensures instrument performance)
3824	pH Buffers; Assorted case of 2 pints each of 4, 7, and 10

Distributed by:

**Lab Unlimited**  
CARL STUART GROUP

Tallaght Business Park  
Whitestown  
Dublin 24  
Ireland

Tel: (01) 4523432  
Fax: (01) 4523967  
E-mail: [info@labunlimited.com](mailto:info@labunlimited.com)  
Web: [www.labunlimited.com](http://www.labunlimited.com)

Unit 59, Frimley House  
35 High Street  
Frimley, Surrey  
GU16 7JQ

Tel: 08452 30 40 30  
Fax: 08452 30 50 30  
E-mail: [info@labunlimited.co.uk](mailto:info@labunlimited.co.uk)  
Web: [www.labunlimited.co.uk](http://www.labunlimited.co.uk)



a xylem brand