



DVNext Rheometer

All-In-One Instrument for Measuring Viscosity + Yield Stress



Quick Set-up with Viscosity Wizard and Digital Leveling



Compliant Versions Include Ethernet and LIMS Connectivity



Single-Handed Spindle Installation and Removal



Optional Compliance to 21 CFR Part 11 in Stand-Alone Mode



Also available in Cone/Plate Version



MODEL COMPARISON	Standard	Compliant
Viscosity Wizard	Included	Included
Digital Leveling	Included	Included
Automated Oscillation Test	Included	Included
Updated Gap Setting	Included	Included
Gel Timer Functions	Included	Included
Magnetic Coupling System	Optional	Included
Barcode Scanning*	Optional	Included
Ethernet Connectivity	N/A	Included
LIMS Connectivity	N/A	Included
Compliance to 21 CFR Part 11	N/A	Included

*Spindle recognition with barcode reader

What's Included

- Instrument
- 6 RV/HA/HB Spindles or 4 LV Spindles
- RTD Temperature Probe
- Spindle Guard Leg*
- Lab Stand (Model G)
- Screen Protector
- Carrying Case

*Not applicable to HA or HB versions



Repeatable



Reliable



Accurate

DVNext Rheometer

All-In-One Instrument for Measuring Viscosity + Yield Stress.
Also Available in Cone/Plate Version.

Features

7-inch Full-Color Touch Screen Display

- Enhanced Controls
- Real-Time Graphing
- Supports Multiple Languages

Displayed Info:

- Viscosity (cP or mPa·s)
- Temperature (°C or °F)
- Shear Rate/Stress %
- Torque Speed/Spindle
- Step Program Status
- Math Model
- Calculations

Viscosity Wizard

Built-in math models for data analysis in stand-alone mode. E.g. Casson, Bingham, Power Law, and Thix Index

Integrated Temperature Control Connected to TC series Baths with AP/SD Controllers or Thermosel System

Stand-alone Programming

RTD Temperature Probe

Accuracy: $\pm 1.0\%$ of Range

- Displayed with test data

Repeatability: $\pm 0.2\%$

Analyze characteristics such as yield stress, flow curves (mixing, pumping, spraying), leveling, and recovery

USB PC Interface provides optional computer control and automatic data collection capability

Internal Data Storage: 150 MB

Date and Time Stamp File

Built-In Options

- Math Modeling
- Temperature Control
- Yield Tests
- Programmable QC Limits, Alarms, End Conditions

Optional Gel Timer functionality using unique magnetic coupling

GAMP*

21 CFR Part 11 Compliant*

- Customizable User Access
- Electronic Signatures
- Uneditable PDFs
- Automated Archived
- Audit Trail

*Only available in Compliant Versions

Optional Accessories

- RheocalcT Software
- Label Printer
- Barcode Scanner
- Ball Bearing Suspension (Standard in high torque instruments)
- Viscosity Standards
- Magnetic Coupling System
- Small Sample Adapter
- UL Adapter
- Spiral Adapter
- DIN Adapter
- Temperature Bath
- Thermosel
- Helipath Stand with T-bar Spindles

VISCOSITY RANGE cP(mPa·s)		SPEEDS (2600 available)	
MODEL	Min.	Max.	RPM Number of Increments
DVNXLV	1†	6M	.01-250 2.6K
DVNXRV	100††	40M	.01-250 2.6K
DVNXHA	200††	80M	.01-250 2.6K
DVNXHB	800††	320M	.01-250 2.6K

†1 cP achieved with UL Adapter accessory. 15 cP on LV with standard spindles.

M = 1 million K = 1 thousand

cP = Centipoise mPa·s = Millipascal-seconds

†† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle



Lab Unlimited
A CALIBRE SCIENTIFIC COMPANY

Carl Stuart Limited
Tallaght Business Park
Whitestown
Dublin 24
D24 RFK3
Ireland

Ph: 00353 1 4523432
Fax: 00353 1 4523967
E-mail: onlinestore@labunlimited.com

Carl Stuart UK Limited
Calibre Scientific UK
Unit 5A, R-Evolution @
The Advanced Manufacturing Park
Selden Way
Rotherham
S60 5XA
United Kingdom

Ph: 08452 30 40 30
Fax: 08452 30 50 30
E-mail: onlinestore@labunlimited.co.uk

