



NEW

ODC-87, ODC-88



Eyepiece camera fixed into the tube

STANDARD



Features

- With the KERN eyepiece cameras you can convert your standard microscope to a digital microscope, by replacing one eyepiece of your non-digital microscope with an eyepiece camera and connect this to your computer via USB.
- The universal eyepiece can be connected to the microscope as well as to a laptop or PC using the USB cable (2.0 or 3.0, see table).
- The power supply is through the USB cable, which means that no additional power supply is required.
- Your daily work is made significantly easier with the very best synchronisation, a high frame rate as well as stable image performance together with our software.
- As well as the camera, the delivery includes a simplified version of our multi-lingual KERN Microscope VIS software, a USB cable and an object micrometer to calibrate the software.

Model	Resolution	Interface	FPS	Sensor	Sensor size	Colour/ Monochrome	Supported operating system
KERN							
ODC 872	1,3 MP	USB 2.0	7,5 – 12,5	CMOS	1/3"	colour	Win XP, Vista, 7, 8, 10
ODC 874	3 MP	USB 2.0	3 – 7,5	CMOS	1/2,7"	colour	Win XP, Vista, 7, 8, 10
ODC 881	5 MP	USB 3.0	15 – 30	CMOS	1/2,5"	colour	Win XP, Vista, 7, 8, 10

USB microscope – USB 2.0 KERN ODC-89



NEW

ODC 894



ODC 895

STANDARD



The digital USB microscope for rapid testing or for hobby use

Features

- The USB hand-held microscope is designed for rapid and simple observations. Ideally suited for coins, plants, insects and skin samples for all hobby scientists, children and students.
- With the USB microscope you can easily adjust the magnification to suit all conventional samples. The zoom range can be adjusted to a magnification of 10× as well as 200×.
- The eight LEDs fitted in the ring shape ensure strong and effective illumination of your sample. Use the adjustment wheel on the cable to control the illumination setting.
- As well as the camera, you will also find a simplified version of our multi-lingual KERN Microscope VIS software included with delivery.
- There are two stands available for you to use as a column.

Stand with integrating coaxial focusing:

- Work area: 150×80 mm
- Focus range: 51 mm
- Overall dimensions: 150×80×147 mm

Stand with focus wheel:

- Work area: 150×80mm
- Focus range: 60 mm
- Overall dimensions: 150×80×135 mm

Model	Resolution	Interface	FPS	Sensor	Sensor size	Supported operating system	Magnification levels	Focusing stand	Illumination
KERN									
ODC 894	2 MP	USB 2.0	15 – 30	CMOS	1/3,2"	Win XP, Vista, 7, 8, 10	10×, 200×	Coaxial	8× LED
ODC 895	2 MP	USB 2.0	15 – 30	CMOS	1/3,2"	Win XP, Vista, 7, 8, 10	10×, 200×	Focus wheel	8× LED

360° rotatable microscope head 360°	Fluorescence illumination for compound microscopes With 3 W LED illumination and filter FL-LED	SD card For data storage SD
Monocular Microscope For the inspection with one eye MONO	Phase contrast unit For a higher contrast PH	PC software To transfer the measurements from the device to a PC. SOFTWARE
Binocular Microscope For the inspection with both eyes BINO	Darkfield condenser/unit For a higher contrast due to indirect illumination DF	Automatic temperature compensation For measurements between 10 °C and 30 °C AUTO ATC
Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera TRINO	Polarising unit To polarise the light POLAR	Protection against dust and water splashes IPxx The type of protection is shown by the pictogram. IP
Abbe Condenser With high numerical aperture for the concentration and the focusing of light ABBE	Infinity system Infinity corrected optical system INFINITY	Battery operation Ready for battery operation. The battery type is specified for each device. BATT
Halogen illumination For pictures bright and rich in contrast HAL	Zoom magnification For stereomicroscopes ZOOM	Battery operation rechargeable Prepared for a rechargeable battery operation RECHARGE
LED illumination Cold, energy saving and especially long-life illumination LED	Parallel optical system For stereomicroscopes, enables fatigue-proof working PARALLEL	Mains adapter 230V/50Hz in standard version for EU. On request GB, AUS or USA version. 230 V
Incident illumination For non-transparent objects IL	Integrated scale In the eyepiece SCALE	Power supply Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request. 230 V
Transmitting illumination For transparent objects TL	Integrated USB 2.0 digital camera For direct transmitting of the picture to a PC USB 2.0	Package shipment The time required to manufacture the product internally is shown in days in the pictogram. 1 DAY
Fluorescence illumination for stereomicroscopes FL	Integrated USB 3.0 digital camera For direct transmitting of the picture to a PC USB 3.0	Warranty The warranty period is shown in the pictogram. 3 YEARS WARRANTY
Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter FL-HBO	HDMI digital camera For direct transmitting of the picture to a display device HDMI	

Abbreviations

C-Mount Adapter for the connection of a camera to a trinocular microscope	LWD Long Working Distance	SWF Super Wide Field (Field number at least Ø 23 mm for 10x eyepiece)
FPS Frames per second	N.A. Numerical Aperture	W.D. Working Distance
H(S)WF High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses)	SLR Kamera Single-Lens Reflex camera	WF Wide Field (Field number up to Ø 22 mm for 10x eyepiece)

Your KERN specialist dealer:

Distributed by:

Lab Unlimited
CARL STUART GROUP

Tallaght Business Park
Whitestown, Dublin 24,
Ireland
D24 RFK3

Tel: (01) 4523432
Fax: (01) 4523967
E-mail: info@labunlimited.com
Web: www.labunlimited.com

Quatro House, Frimley Road,
Camberley,
United Kingdom
GU16 7ER

Tel: 08452 30 40 30
Fax: 08452 30 50 30
E-mail: info@labunlimited.co.uk
Web: www.labunlimited.co.uk